PIKOLINE® Source of Professional Products

SAFETY DATA SHEET of:

PikoDes Para

Revision date: Wednesday, December 16, 2020

S96.50

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

PikoDes Para

UFI: 7D10-V0NN-R00W-87M9

1.2 Relevant identified uses of the substance or mixture and uses advised against:

/

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

Pikoline BV

Kruisdonk 66

6222 PH Maastricht

Phone: +31432041190 — E-mail: info@pikoline.com — Website: http://www.pikoline.com/

1.4 Emergency telephone number:

+31 432 04 11 90

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

H226 Flam. Liq. 3 H290 Met. Corr. 1 H314 Skin Corr. 1B H317 Skin Sens. 1 H335 STOT SE 3 H336 STOT SE 3

2.2 Label elements:

Pictograms:



Signal word:

Danger

Hazard statements:

H226 Flam. Liq. 3: Flammable liquid and vapour. **H290 Met. Corr. 1:** May be corrosive to metals.

H314 Skin Corr. 1B: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.
 H335 STOT SE 3: May cause respiratory irritation.
 H336 STOT SE 3: May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P233: Keep container tightly closed.

P280: Wear protective gloves, protective clothing, eye protection, face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.
P403+P235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container in accordance with local/regional/national/international

regulations.

Contains:

Phosphoric acid Isopropanol 3-Methyl-4-Chlorophenol Dodecylbenzenesulphonic acid

2.3 Other hazards:

None

3 SECTION 3: Composition/information on ingredients:

Isopropanol	≤ 30 %	CAS number: EINECS: REACH Registration number: CLP Classification:	67-63-0 200-661-7 01-2119457558-25 H225 Flam. Liq. 2 H319 Eye Irrit. 2 H336 STOT SE 3
3-Methyl-4-Chlorophenol	≤ 30 %	CAS number: EINECS: REACH Registration number: CLP Classification:	59-50-7 200-431-6 H302 Acute tox. 4 H312 Acute tox. 4 H317 Skin Sens. 1 H318 Eye Dam. 1 H400 Aquatic Acute 1
Phosphoric acid	≤ 20 %	CAS number: EINECS: REACH Registration number: CLP Classification:	7664-38-2 231-633-2 01-2119485924-24 H290 Met. Corr. 1 H302 Acute tox. 4 H314 Skin Corr. 1B

Dodecylbenzenesulphonic acid	≤ 20 %	CAS number:	85536-14-7
		EINECS:	287-494-3
		REACH Registration number:	01-2119490234-40
		CLP Classification:	H302 Acute tox. 4 H314 Skin Corr. 1B H412 Aquatic Chronic 3
Propionic acid	≤9%	CAS number:	79-09-4
		EINECS:	201-176-3
		REACH Registration number:	01-2119486971-24
		CLP Classification:	H314 Skin Corr. 1B

For the full text of the H phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: Remove contaminated clothing, rinse skin with plenty of water and immediately

transport to hospital.

Eye contact: Thoroughly rinse with water (contact lenses to be removed if this is easily done) then

take to physician.

Ingestion: Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact:Caustic, redness, pain, serious burnsEye contact:Caustic, redness, blurred vision, pain

Ingestion: Caustic, lack of breath, vomiting, blisters on lips and tongue, burning pain in mouth

and throat, gullet and stomach

Inhalation: Headache, dizziness, nausea, drowsiness, unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed:

None

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

CO2, foam, powder, sprayed water

5.2 Special hazards arising from the substance or mixture:

None

5.3 Advice for firefighters:

Extinguishing agents to be

None

avoided:

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

6.4 Reference to other sections:

For further information, check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

/

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

Isopropanol 424 mg/m³, Propionic acid 31 mg/m³, Phosphoric acid 1 mg/m³

8.2 Exposure controls:

Inhalation protection:	Use with sufficient exhaust ventilation. If necessary, use an air-purifying face mask in case of respiratory hazards. Use the ABEK type as protection against these troublesome levels.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range:

Boiling point/Boiling range: 82 °C — 142 °C

pH:

pH 1% diluted in water: 2.1

Vapour pressure/20°C,: 4 300 Pa

Vapour density:

Relative density, 20°C:

Appearance/20°C:

Not applicable
1.1150 kg/l
Liquid

Flash point: 32 °C

Flammability (solid, gas): Not applicable

Auto-ignition temperature: 370 °C
Upper flammability or explosive 12.000 %

limit, (Vol %):

Lower flammability or explosive

limit, (Vol %):

2.000 %

Explosive properties: Not applicable

Oxidising properties: Not applicable

Decomposition temperature: /

Solubility in water: Completely soluble

Partition coefficient: n- Not applicable

octanol/water:

Odour: characteristic
Odour threshold: Not applicable

Dynamic viscosity, 20°C: 1 mPa.s

Kinematic viscosity, 40°C: 1 mm²/s

Evaporation rate (n-BuAc = 1): 1.300

9.2 Other information:

Volatile organic component (VOC): 36.50 % Volatile organic component (VOC): 406.975 g/l

Sustained combustion test: /

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

Stable under normal conditions.

10.2 Chemical stability:

Extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

None

10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

Acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

H314 Skin Corr. 1B: Causes severe skin burns and eye damage.

H317 Skin Sens. 1: May cause an allergic skin reaction.
 H335 STOT SE 3: May cause respiratory irritation.
 H336 STOT SE 3: May cause drowsiness or dizziness.

Calculated acute toxicity, ATE oral: 1 003.838 mg/kg

Calculated acute toxicity, ATE

dermal:

Isopropanol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
3-Methyl-4-Chlorophenol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	600 mg/kg 1 100 mg/kg ≥ 50 mg/l
Phosphoric acid	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	500 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Dodecylbenzenesulphonic acid	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	1 150 mg/kg ≥ 5 000 mg/kg ≥ 50 mg/l
Propionic acid	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5 000 mg/kg 3 235 mg/kg ≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

Isopropanol	LC50 (Fish): LC50 (Daphnia):	10000 mg/l > 10000 mg/L (24h)
3-Methyl-4-Chlorophenol	LC50 (Fish): EC50 (Daphnia): EC50 (Algae):	6,71 - 7,56 mg/L (4d) 1.5 mg/L (48h) 10 mg/L (4d)
Phosphoric acid	EC50 (Daphnia): NOEC (Daphnia): EC50 (Algae): NOEC (Algae):	100 mg/L (48h) 56 mg/L (48h) 100 mg/L (72h) 100 mg/L (72h)
Dodecylbenzenesulphonic acid	LC50 (Fish): NOEC (Fish):	> 1 -10 mg/l (Lepomis macrochirus) (96h) 1 mg/l (Lepomis macrochirus) (28d)

Propionic acid	LC50 (Fish):	10 g/L (4d)
	NOEC (Fish):	5 g/L (4d)
	EC50 (Daphnia):	500 mg/L (48h)
	NOEC (Daphnia):	250 mg/L (48h)
	EC50 (Algae):	500 mg/L (72h)

12.2 Persistence and degradability:

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3 Bioaccumulative potential:

	Additional data:
Isopropanol	Log Pow: 0.05
Dodecylbenzenesulphonic acid	log Pow = 2
Propionic acid	Log Pow = 0,29 - 0,33 @ 25 °C

12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 2

Solubility in water: Completely soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

Draining into the sewers is not permitted. Removal should be carried out by licensed services. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

2924

14.2 UN proper shipping name:

UN 2924 Flammable liquid, corrosive, n.o.s. (mixture with Isopropanol; Phosphoric acid), 3 (8), III, (D/E)

14.3 Transport hazard class(es):

Class(es): 3 (8)
Identification number of the 38

hazard:

14.4 Packing group:

Ш

14.5 Environmental hazards:

Not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: Risk of fire. Risk of explosion. Containments may explode when heated.

Additional guidance: Take cover. Keep out of low areas.





15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 2

Volatile organic component (VOC): 36.500 % Volatile organic component (VOC): 406.975 g/l

Composition by regulation (EC)

648/2004:

Anionic surfactants 15% - 30%, Preservatives (3-Methyl-4-Chlorophenol)

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate
BCF: Bioconcentration factor
CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

LD50: median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative

TLV: Threshold Limit Value
UFI: Unique Formula Identifier

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

WGK 1: Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

Legend to the H Phrases used in the safety data sheet:

H225 Flam. Liq. 2: Highly flammable liquid and vapour.
H290 Met. Corr. 1: May be corrosive to metals.
H312 Acute tox. 4: Harmful in contact with skin.
H314 Skin Corr. 1B: Causes severe skin burns and eye damage.
H317 Skin Sens. 1: May cause an allergic skin reaction.
H318 Eye Dam. 1: Causes serious eye damage.
H319 Eye Irrit. 2: Causes serious eye irritation.
H335 STOT SE 3: May cause drowsiness or dizziness.
H400 Aquatic Acute 1: Very toxic to aquatic life.
H412 Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

CLP Calculation method:

Calculation method

Reason of revision, changes of following items:

Section: 15.1

SDS reference number:

ECM-111603,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.